

SafeView

OTHER SYSTEMS



Professional double channel rear view kit for the surveillance of partially or totally blind areas. System provides a panoramic high resolution vision also in absence of light.

V HIGH QUALITY IMAGE

V SUITS TO A WIDE RANGE OF INDUSTRIAL VEHICLES

V WATERPROOF IR BALL CAMERA

✓ COMPACTNESS FOR EASY ON-BOARD INTEGRATION

COMPLETE SYSTEM SafeView



System provides an integrated DC/DC converter for maximum versatility. The system architecture, with all the connection with the vehicle starting from the powerbox, makes installation quick and easy. The pre-made molded connection between the modules guarantee the maximum connection reliability.

KIT CONTENT

Monitor kit inclusive of:

- 5" monitor;
- universal bracket.

Camera kit inclusive of:

- IR Ball camera;
- 3 m connecting cable;
- bracket, screws, bolts, washers kit.

Powerbox kit inclusive of:

- powerbox/splitter with channel change and voltage reduction function.

GENERAL FEATURES				
Operating voltage	12-48VDC			
Triggering voltage	12-48VDC			
Operating current	500mA max			
Number of cameras (max)	2 (with automatic triggering)			
Operating temperature	-30°C / +70°C			

MONITOR TECHNICAL FEATURES		CAMERA TECHNICAL FEATURES	
Screen dimensions	5"	View angle	110°
TFT	TFT	Resolution	500x582 pixels
Ratio	4:3	IP rating	IP68
Resolution	307x200 pixels	Night view	15 infrared leds
Brightness	200 cd/m^2	Night view distance	8m max
Outline dimensions	126.5mm x 100mm x 15mm		





IP rating

Forklift Safety Solutions

IP50

Unit 5, Tamworth Enterprise Park, Lichfield Road Ind. Est, Tamworth, B79 7UL Email : sales@forklift-safety.co.uk Tel : 07967 190970